

3.20Z WOVEN GROUND COVER AND WEED FABRIC

GRADE A - GEOTEXTILE

TECHNICAL SPECIFICATIONS PRODUCT DATA SHEET

Property	TEST METHOD	Typical English*	Typical Metric*
Weight	ASTM D3776	3.2 oz/yd^2	108 g/m^2
Tensile Strength (Grab)	ASTM D4632	175 x 120 lbs	800 N x 550 N
Elongation (Grab)	ASTM D4632	25%	25%
Trapezoidal Tear Strength	ASTM D4533	85 x 70 lbs	390 N x 320 N
CBR Puncture	ASTM D6241	500 lbs	2290 N
UV Resistance (2500 hrs)	ASTM D4355	80%	80%
UV		4%	4%
Water Flow Rate	ASTM D4491	15 gpm/ft ²	

^{*} Minimum Average Roll Value

PROPERTY			
Fabric Color Options Available	Black	White	Green
Stripe Color	White	Black	Black
Stripe Spacing	Every 12 inches	Every 12 inches	Every 12 inches

Agtec assumes no liability for the completeness, accuracy or ultimate use of this information. Agtec disclaims any and all implied, expressed, or statutory standards, guarantees, or warranties, including without limitation any implied warranty as to merchantability or fitness for a particular purpose or arising from a course of dealing or usage of trade as to equipment, materials, or information furnished herewith. This document should not be construed as engineering advice. Always consult a project engineer for project specific requirements. End user assumes sole responsibility for the use of this information and product. Property values listed here are subject to change without notice.

- www.agtec.com sales@agtec.com 1-207-692-0700
 - Agtec LLC, 125 Mayo Road, Hampden Maine 04444