



# NON WOVEN 4.5OZ FILTER & DRAINAGE FABRIC

## TECHNICAL SPECIFICATIONS PRODUCT DATA SHEET

PROPERTY	TEST METHOD	TYPICAL ENGLISH	TYPICAL METRIC
Weight	ASTM D3776	4.5 oz/yd <sup>2</sup>	g/m <sup>2</sup>
Tensile Strength (Grab)	ASTM D4632	120 x 120 lbs	534 x 534 N
Elongation (Grab)	ASTM D4632	50% x 50%	50% x 50%
Trapezoidal Tear Strength	ASTM D4533	50 x 50 lbs	222 x 222 N
CBR Puncture	ASTM D6241	335 lbs	1,490
UV Resistance (2500 hrs)	ASTM D4355	70%	70%
Apparent Opening Size (Maximum Typical Roll Valve)	ASTM D4751	70 US Std. Sieve	0.212 mm
Permittivity	ASTM D4491	1.7 sec <sup>-1</sup>	1.7 sec <sup>-1</sup>
Water Flow Rate	ASTM D4491	120 gpm/ft <sup>2</sup>	4,889 lpm/m <sup>2</sup>

PROPERTY				
Fabric Color	Black			
Stripe Color	None			
Roll Dimensions	3ft x 360ft	3ft x 120ft	.914m x 109.8m	.914m x 36.6m
	4ft x 360ft	4ft x 120ft	1.2m x 109.8m	1.2m x 36.6m
	6ft x 360ft	6ft x 120ft	1.8m x 109.8m	1.8m x 36.6m

Agtec assumes no liability for the completeness, accuracy or ultimate use of this information. Agtec disclaims any and all implied, expressed, or statutory standards, guarantees, or warranties, including without limitation any implied warranty as to merchantability or fitness for a particular purpose or arising from a course of dealing or usage of trade as to equipment, materials, or information furnished herewith. This document should not be construed as engineering advice. Always consult a project engineer for project specific requirements. End user assumes sole responsibility for the use of this information and product. Property values listed here are subject to change without notice.

- [www.agtec.com](http://www.agtec.com) • [sales@agtec.com](mailto:sales@agtec.com) • 1-207-692-0700 •
- Agtec LLC, 125 Mayo Road, Hampden Maine 04444 •